



# Grindex Electrical Submersible Pumps



Dewatering and Sludge Pumps  
Corrosion Resistant Pumps  
Slurry Pumps

### Small Dewatering and Sludge Pumps

Lightweight, portable and compact dewatering and sludge pumps.

Max Flow: 100 gpm  
Max Head: 53 ft.  
Power: 0.6-1.1 HP



### Submersible Dewatering Pumps

Lightweight, portable and compact dewatering pumps for professional use. MSHA version as an option.

Max Flow: 5,000 gpm  
Max Head: 750 ft.  
Power: 1.9-140 HP



### Submersible Sludge Pumps

Lightweight, portable and compact sludge pumps for professional use.

Max Flow: 440 gpm  
Max Head: 125 ft.  
Power: 2.4-8.9 HP



### Corrosion Resistant Dewatering Pumps

Dewatering pumps in stainless steel for corrosive applications.

Max Flow: 1,000 gpm  
Max Head: 250 ft.  
Power: 3.1-13 HP



### Corrosion Resistant Sludge Pumps

Sludge pumps in stainless steel for corrosive applications.

Max Flow: 550 gpm  
Max Head: 80 ft.  
Power: 3.1-9 HP



### Submersible Slurry Pumps

Slurry pumps in Ni-Hard for maximum wear resistance. Comes with or without agitator.

Max Flow: 2,500 gpm  
Max Head: 120 ft.  
Power: 5.4-73.7 HP



### Typical Applications:

Construction

Tunnelling

Mining

Mineral Processing

Sand & Gravel

Cement Industry

Municipalities

Steel Industry

Power Plants

Marine & Offshore Industry

Shipyards

Marine Salvage Industry

Marine Construction

Landfills

Food & Beverage

Aquaculture Industry

Ethanol Industry

Utilities

Chemical Industry

Oil & Gas Industry

Water Features & Parks