


VTP & VPC

Vertical Turbine

Wet Pit and Double Casing Pumps

MAINTENANCE CHECKLIST



! DANGER

Read User Instructions **before** installing, operating or maintaining this pump.
Copies available from Flowserve pump representative.

Operating Limits

Pumped Liquid Temperature Limits*	5°C (40°F) to +80°C (176°F)
Maximum Ambient Temperature*	Up to +40°C (104°F)
Maximum Pump Speed	Refer to the Nameplate

* Subject to written agreement from Flowserve. Special designs and materials may be available for pumps operating above and below these specified limits. Contact Flowserve for upgrade options available for your specific application.

Impeller Clearance Settings

Flowserve recommends the following impeller settings based on the pump sizes.

If the Pump Size Is:	Setting for Enclosed Impellers	Setting for Semi-Open Impellers
Size 6 thru size 12	3~4 mm (0.13~0.15 in)	0.25 mm to 0.38 mm (0.010 in to 0.015 in)
Size 14 and above	6~7 mm (0.25~0.27 in)	0.63 mm to 0.76 mm (0.025 in to 0.030 in)

Note: Shafts elongate due to the hydraulic thrust of the pump and the impellers must be compensated for this elongation. Shaft elongation varies for each model depending upon the size, shaft length, shaft diameter, impeller weight, number of stages. Please see the documentation supplied along with the pump for exact impeller setting value matched for the specific pump that you have purchased

Shaft / Bearing Clearance

Shaft Size mm (in)	Shaft Diameter/Tolerance (Min Dia - Max Dia) mm (in)		Bearing Clearance (Max/Min) mm (in)
	Min Dia	Max Dia	
25.40 (1.000)	25.35 (0.998)	25.40 (1.000)	0.28/0.13 (0.011/0.005)
31.75 (1.250)	31.70 (1.248)	31.75 (1.250)	0.35/0.15 (0.012/0.006)
38.10 (1.500)	38.05 (1.498)	38.10 (1.500)	0.33/0.18 (0.013/0.007)
42.86 (1.690)	42.81 (1.685)	42.86 (1.687)	0.36/0.18 (0.014/0.007)
49.21 (1.940)	49.16 (1.935)	49.21 (1.937)	0.38/0.23 (0.015/0.008)
55.56 (2.190)	55.51 (2.185)	55.56 (2.187)	0.41/0.23 (0.016/0.009)
61.91 (2.440)	61.86 (2.435)	61.91 (2.437)	0.41/0.23 (0.016/0.009)
68.26 (2.690)	68.21 (2.685)	68.26 (2.687)	0.43/0.23 (0.017/0.009)
74.61 (2.940)	74.56 (2.935)	74.61 (2.937)	0.43/0.23 (0.017/0.009)
82.55 (3.250)	82.47 (3.247)	82.55 (3.250)	0.46/0.25 (0.018/0.010)
88.90 (3.500)	88.82 (3.497)	88.90 (3.500)	0.48/0.28 (0.019/0.011)
95.25 (3.750)	95.17 (3.747)	95.25 (3.750)	0.53/0.35 (0.021/0.012)
101.60 (4.000)	101.58 (3.997)	101.60 (4.000)	0.56/0.33 (0.022/0.013)
114.30 (4.500)	114.22 (4.497)	114.30 (4.500)	0.58/0.35 (0.023/0.014)
127.00 (5.000)	126.92 (4.997)	127.00 (5.000)	0.61/0.38 (0.024/0.015)

USA and Canada

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 2300
Irving, Texas 75039-5421 USA
Telephone: 1 937 890 5839

Europe, Middle East, Africa

Flowserve Corporation
Gebouw Hagepoint
Westbroek 39-51
4822 ZX Breda
Netherlands
Telephone: 31 76 502 8920

Latin America

Flowserve Corporation
Boulevard del Cafetal
Edificio Ninina, Local 7
El Cafetal - Caracas
Venezuela 1061
Telephone: 58 212 985 3092
Telefax: 58 212 985 1007

Asia Pacific

Flowserve Pte. Ltd.
10 Tuas Loop
Singapore 637345
Telephone: 65 6771 0600
Telefax: 65 6779 4607

For sales product information, go to www.flowserve.com

Bolt Torque Values for Class 2 Lubricated Treads

Thread Data		Material Group					
		A 316 SS	B ASTM B164 UNS N04400	C Hastelloy C276	D ASTM A449 Grade 5	E ASTM A193 Grade B7M	F SAE J429 Grade 8
		Approximate Yield Stress – N/mm ² (psi)					
Nominal Diameter	Threads Per 25 mm/1 in	207 (30000)	276 (40000)	345 (50000)	441 (60000)	552 (80000)	690 (100000)
mm (in)		Torque Nm (lb-ft)					
6 (0.25)	20	4 (3)	5 (4)	5 (4)	7 (5)	9 (7)	12 (9)
8 (0.31)	18	7 (5)	8 (6)	11 (8)	14 (10)	17 (13)	21 (16)
10 (0.37)	16	9 (7)	14 (10)	16 (12)	20 (15)	27 (20)	34 (25)
11 (0.43)	14	16 (12)	20 (15)	25 (19)	31 (23)	42 (31)	53 (39)
12 (0.50)	13	23 (17)	31 (23)	39 (29)	47 (35)	62 (46)	78 (58)
15 (0.56)	12	27 (20)	45 (33)	75 (41)	66 (49)	89 (66)	111 (82)
16 (0.62)	11	41 (30)	60 (44)	54 (73)	88 (65)	118 (87)	149 (110)
19 (0.74)	10	81 (60)	101 (75)	127 (94)	149 (110)	203 (150)	257 (190)
22 (0.87)	9	122 (90)	163 (120)	203 (150)	258 (190)	312 (250)	420 (310)
25 (1.00)	8	190 (140)	244 (180)	312 (230)	366 (270)	488 (360)	610 (450)
29 (1.13)	7	271 (200)	352 (260)	448 (330)	529 (390)	705 (520)	882 (650)
29 (1.13)	7	271 (200)	366 (270)	461 (340)	556 (410)	732 (540)	923 (680)
32 (1.25)	7	366 (270)	488 (360)	610 (450)	746 (550)	990 (730)	1235 (910)
32 (1.25)	8	379 (280)	502 (370)	637 (470)	760 (560)	1017 (750)	1275 (940)
35 (1.38)	6	434 (320)	570 (420)	719 (530)	855 (630)	1140 (840)	1425 (1050)
35 (1.38)	8	461 (340)	610 (450)	760 (560)	922 (680)	1221 (900)	1533 (1130)
38 (1.50)	6	556 (410)	746 (550)	936 (690)	1126 (830)	1506 (1110)	1872 (1380)
38 (1.50)	8	597 (440)	800 (590)	990 (730)	1194 (880)	1587 (1170)	1995 (1470)
41 (1.63)	5.5	719 (530)	963 (710)	1207 (890)	1438 (1060)	1927 (1420)	2402 (1770)
41 (1.63)	8	773 (570)	1031 (760)	1302 (960)	1560 (1150)	2076 (1530)	2592 (1910)
44 (1.75)	5	882 (650)	1180 (870)	1479 (1090)	1778 (1310)	2375 (1750)	2958 (2180)
44 (1.75)	8	971 (720)	1302 (960)	1628 (1200)	1940 (1430)	2592 (1910)	
50 (2.00)	4.5	1356 (1000)	1778 (1310)	2225 (1640)	2673 (1970)		
50 (2.00)	8	1478 (1090)	1968 (1450)	2470(1820)	2958 (2180)		
57 (2.25)	8	2143 (1580)	2850 (2100)				
63 (2.50)	8	2970 (2190)					

Leveling:

The pump discharge head and mounting surface shall be leveled within 0.025 mm / 0.31 m (0.001 in/ft). The level shall not exceed 0.125 mm (0.005 in) elevation difference between any two points.

Enclosed Lineshaft – Oil Lubricated

Non-Food Grade Lubricant Oils

Oil Manufacturer	Trade Name of the Oil
Conoco Inc.	Conoco Diamond Class Turbine Oil (ISO 32)
Exxon Company	Teresstic GT 32
Mobil Oil Company	Mobile DTE-797 (Grade-32)
Shell Oil Company	Tellus-32, Tellus-37 or Turbo Oil T-32
Chevron Lubricants	Chevron Turbine Oil TR-32
BP	Energol HL-C 32
Texaco, Inc.	Texaco Regal R&O 32

Notes:

Viscosity = 30-37 cSt

Amount = 3 drops per minute per 30 m (100 ft) not to exceed 5 drops per minute.

Prelubrication = 45 minutes prior to pump start-up

Food Grade Lubricant Oils

Oil Manufacturer	Trade Name of the Oil
Exxon Company	Exxon-DTE-FM32
Mobil Oil Company	Mobile DTE-FM-Grade-32
Shell Oil Company	Cassida HF 32

Pump / Motor Coupling Fastener Torques

Coupling Size #	Flange Diameter mm (in)	Nm (lb ft)
1 & 2	111 or 137 (4.4 or 5.4)	122 (90)
3-5	156, 187, 213 (6.0, 7.4, 8.4)	237 (175)
6	250 (10.0)	424 (313)

Torque values are for standard fasteners lubricated with a high stress lubricant (such as graphite and oil, molydisulphite, white lead, etc.). For stainless steel bolts, multiply listed torques by 0.80.

Alignment:

Total indicated runout (TIR) shall not exceed 0.25 mm (0.010 in) for WA and WSA couplings or 0.15 mm (0.006 in) for PA and PSA couplings.

Enclosed Lineshaft – Fresh Water Injection

Notes:

Amount = 0.45-0.90 m³/h (2-4 gpm) at 0.7-1.4 bar (10-20 psi) over the maximum discharge pressure*

Type = Clean city water

Prelubrication = 10-20 minutes prior to pump start-up

* In certain cases, only 0.7-1.4 bar (10-20 psi) of total pressure is required. Contact factory for review.